

# Fireattack

## F25

www.fireattack.net

**BEST  
FEATURE/  
PICTURES**



**BEST  
PRICE**

- 256x192
- Hz25
- Modes
- Super IR
- Photo/Video

- Display 3.2"
- mK 30
- Zoom 2x/4x
- ODE
- Wifi

Smooth Mode

# Fireattack

## F120

www.fireattack.net



- 4,3" / 60 Hz
- 650 ° / 1.200 °C
- 2/4 Zoom
- OD
- Wifi

- 35 mK
- 6 Modes
- 384 x 288 Resolution
- Foto / Video

**SET: F25 + TRUCK CHARGER +  
RETRACT + NECK STRAP  
EIN PREIS – ONE PRICE**

**NFPA 1801  
KONFORM**

**TAKTIK /  
UVA-CAM**

**DFV-AGBF  
FACHEMPFEHLUNG  
KONFORM**

## KEY FEATURES

- Resolution – Thermal resolution: 384 x 288 (110,592 pixels)
- NETD: <35 mK (@ 25 °C, F#=1.0)
- Start time – Start up time: 5 seconds (with IR image), 10 seconds (with OSD)
- Image support for object details - OD
- Temperature measurement range: -20 °C to 1200 °C / NFPA -20 °C – 650 °C
- Measurement presets: Center spot, Hot spot, Cold spot
- 60 Hz image frequency
- 4.3" LCD screen display
- Hot and Cold Tracker
- 6 Modes – NFPA Basic, White Hot, Black Hot, Fire Detection, Rescue, Hot Area
- Photo / Video storage 32 GB or Freeze function
- 2x / 4x Zoom
- Wi-Fi function switchable
- Date and time optionally switchable
- Compass switchable

## 3 IN 1-THERMALCAM

The Fireattack is a robust, compact, and high-quality thermal imaging camera designed for tough firefighting operations. In darkness, smoke, and many other situations, the camera helps save lives, protect property, and ensure the safety of firefighters. The individual configuration of the F120 is protected by a custom-set three-digit password. This way, you as the user decide whether you want to use a one-button, two-button, or three-button camera.

You decide whether to have more than one mode, zoom, photo-video storage, hot/cold tracker, and which Tempbar display and storage type are used. It is a handheld thermal imaging camera from the attack AOR, tactical, tactical UVA range, designed to be held with one hand. The three buttons of the camera can be easily operated with one finger. It is equipped with image support and many features.

There is always the possibility to use photo and video recording or the freeze function – in addition to the various image modes that assist the user in their different activities. It has 2x and 4x zoom, which, together with the Black White

(BW) mode, can optimally support person search. The Hot and Cold Tracker provides the user with important information at any time. The display with 4.3", 60 Hz, resolution of 384 x 288, the value of 35 mK (0.035 °C), a representation of 650 °C or up to 1200 °C, and the OD system ensure clear and detailed image representation at all times.

The IP67 rating, 2 m drop test, 260 °C with up to 7 minutes operating temperature range, reliably ensure the use of the F120 even under the most extreme conditions. The date and time can optionally be displayed continuously on the screen, which is, for example, ideal for training centers or for documentation. The optional Wi-Fi function gives you the possibility of live image transmission. In addition, a compass can optionally be activated, for example for wildland firefighting.

With these possibilities, the 3-in-1 camera, configurability, technical specifications, and the price-performance ratio, the camera is without equal.

## F25 – THE THERMAL CAMERA FOR EVERY OPERATOR

**FIREATTACK F25 THE AOR/ATTACK CAMERA AND AS A LITTLE BROTHER OF THE FIREATTACK F120**  
**SMALL – COMPACT – CONFIGURABLE – SIMPLE**  
**COST-EFFECTIVE – OPTIMAL PERFORMANCE**  
**LATEST TECHNOLOGY**

Every operator in respiratory protection, whether attack team or safety team, should carry a personal thermal imaging camera with them. To use the sixth sense in operational situations. And to ensure optimal safety for themselves as rescuers and for those to be rescued.

The F25 is suitable for indoor attack, robust, heat-resistant, IP67 and operable with firefighter gloves according to DIN EN 659. With the built-in sensors and a resolution of 256 x 195 pixels and a field of view of 37.2° x 50°, it produces a more compact, detailed representation of the operational scene. This is further optimized by the OD and Super IR image support. The SmoothMode compensates for the switching process during image calibration, thereby enabling continuous thermal imaging. You can also use the F25's flashlight during operation without using the thermal imaging camera. This way, you always have a flashlight on hand during operations.

The F25 is excellent for use with the hot tracker for locating smoldering nests in the context of vegetation fire fighting. As with the Fire-attack F120, you can configure the F25 according to your needs and protect this for the user with your own set password. The 2x and 4x zoom as well as the different image modes and the photo/video function complete the technical features. The Wi-Fi function allows, for example, the incident commander to observe the operation live.

You can also modify the F25 to be a pure On/Off camera, it is up to you how you use the camera. One price for all functions.

- Resolution: 256x192
- Display: 3.2"
- Hz: 25
- mK: 30
- Weight: 398 g
- Zoom: 2x – 4x
- Modes: Basic Fire, BW, WB, Smooth, Hot Area, Rescue, Fire Detection
- Hot & Cold Tracker
- Image support ODE and Super IR
- Photo and video storage
- Wifi



## WHAT DOES THE F120 EXCLUSIV DO?

The Fireattack F120 has been specifically developed for fire services. With its own three-digit password protection, you can configure the F120 as an attack (AOR), tactical, or tactical-UVA camera.

**THE F120 IS THE THREE-IN-ONE CAMERA!  
 YOU DECIDE HOW YOU WANT  
 TO USE THE CAMERA.**

... and all at one price!



- Switching from high to low gain ≤ 1 sec.
- ONLY FIRE SERVICE SPECIFIC MODES
- Configuration of the F120 can be individually protected with its own three-digit password.
- Configurable as
  - One-button camera – only On and Off attack camera
  - Two-button camera – On/Off – Zoom or On/Off – Mode
  - Three-button camera – On/Off – Zoom – Mode
 Additionally, the use of the trigger as Photo/Video – Freeze – no function

- Two temperature ranges in one camera -20 ° ->650 ° and >1200 °
- NFPA mode with a display of -20 ° ->650 °
- Basic / NFPA mode with standard display according to NFPA (Battery/Temp bar... symbols)
- OD image support always on
- NFPA/BASIC mode always as start mode ON/OFF button pressed for 3 seconds Standby / 6 seconds Off. The status is displayed to the user on the display.
- ON/OFF switch serves as a reset switch – Always return to NFPA/Basic Mode –
- For the Hot and Cold Tracker, the temperatures are displayed directly at the measurement point
- Date and time optionally switchable

## WHAT DOES THE F25 EXCLUSIV DO?

- Start from the Smooth System or BASIC / NFPA mode definable
- Photo / video storage definable
- Best image support always enabled
- No double assignment of keys
- Small display of the hot and cold tracker possible
- Fire department-related modes and usage
- Password protection only for the settings menus

## 6 MODES FOR ALL SITUATIONS



**TRUCK CHARGER**  
**12V/24V/USB-C/230V**

**MEHRERE MITEINANDER VERBINDBAR /  
 MULTIPLE CAN BE CONNECTED WITH EACH OTHER**

**PRICE - PREISE**



**RETRACT  
 NECK STRAP**

Mehr Informationen unter  
[www.fireattack.net](http://www.fireattack.net)  
 More informations at  
[www.fireattack.net](http://www.fireattack.net)

